

## Karakteristike kola H

NAZIV		Habis	Hbis	Hbbikks	Hbfkks	Hfkks
		275 0...	225 0...	237 0...	239 0...	219 1...
Broj osovina		4	2	2	2	2
Razmak stoz. obr. post	m	1,544	-	-	-	-
Razmak krajnjih osovina	m	1,724	800	900	800	570
Duzina preko odbojnika	m	2,046	1,461	1,640	1,403	1,064
Korisna duzina poda	m	2 x 9,27	1,271	1,493	1,273	934
Korisna sirina poda	m	266	267	260	226	235
Korisna površina poda	m <sub>2</sub>	4,930	3,390	3,880	2,880	2,190
Korisna zapremina	m <sub>3</sub>	11,340	8,000	8,540	66,620	5,040
Broj vrata		8	4	6	2	2
Utovarna sirina vrata	m	481	624	503	200	200
Utovarna visina vrata	m	220	207	240	200	200
Maksimalna širina otvora vrata	m	942	624	1,006	200	200
Visina poda iznad GIS-a	m	123	120	120	123	125
Brao pregrada u kolima		40	-	-	-	-
Sopstvena masa kola	t	265	13	1,550	1,410	11,10-12,4
Granica tovarenja A	t	375	1,900	1,650	1,750	1,950
Granica tovarenja B	t	4,550	2,300	2,050	2,150	2,350
Granica tovarenja C	t	5,350	2,700	2,450	2,150	2,350
S A	t	3,750	1,900	1,650	1,750	1,950
S BC	t	4,550	2,300	2,050	2,150	2,350
SS ABC	t	-	-	-	-	-
Rezim razmene		RIV	RIV	RIV	RIV	RIV
Napomena		12	1	1	1	1